Technical Report

Professional Services Delaware Valley Regional Planning Commission New Jersey Traffic Signal Retiming Initiative

Sweetbriar Avenue/Sloan Avenue Mercer County Route 649

From Whitehead Road (CR 616) to Klockner Avenue, NJ Transit Hamilton Rail Station,

In Hamilton Township, Mercer County, NJ

May 2022

Prepared For:







Prepared By:









I. Summary

A. Project Overview

Under contract with Delaware Valley Regional Planning Commission (DVPRC), in cooperation with Mercer County and the New Jersey Department of Transportation, the Taylor Wiseman & Taylor (TWT) project team has completed traffic signal retiming work at four (4) signalized intersections along Sweetbriar Avenue/Sloan Avenue (Mercer County Route 649), in Hamilton Township, Mercer County. This work started in May 2018, following completion of Phase 1 of the contract which evaluated candidate corridors within Mercer County and established a consensus priority list. In accordance with the process jointly established by DVRPC, Mercer County and the TWT team, updated timing plans, including adjustments to cycle lengths, splits, and offsets, as well as the introduction of additional time-of-day coordination patterns, were implemented by March 20, 2022.

This project involved extensive traffic data collection, including automatic traffic recorder counts, peak hour turning movement counts, controller assessments and 'before' travel time runs. The collected data was analyzed using traffic engineering software including Synchro™ and Tru-Traffic™. New timing plans were developed for the corridor, which were implemented by the consultant team in March 2022. Fine-tuning and field observations were conducted throughout implementation, resulting in minor timing changes to those initially implemented. Final travel time runs were completed, and comparisons made to the 'before' condition. This report summarizes the activities, observations and results of this project.

B. Results

With implementation of the 1) updated timing plans, and 2) modifications to the corridor's time-of-day schedule, the TWT team has documented significant reductions in corridor travel times and delay. The Sweetbriar



Photo 1: Looking EB at Hamilton Rail Station/Klockner Road

Cumulative delay on the Sweetbriar Avenue/Sloan Avenue corridor was reduced 94% during the typical weekday mid-day period.

Avenue/Sloan Avenue corridor is arguably two corridors, as the traffic characteristics associated with the eastern signals on the corridor are more peak-hour oriented than Vetterlein Avenue, or even Whitehead Road. Nevertheless, the TWT team reduced overall weekday morning, mid-day, evening and weekend mid-day peak travel times by 17%, 22%, 25%, and 27%, respectively. Cumulative

delay on the corridor was impacted more dramatically, as overall weekday morning, mid-day, evening and weekend delays were reduced by 47%, 94%, 85% and 85%. Summary results for the corridor are presented in **Table 1**. Detailed results, showing a further breakdown of this data is presented later in this report. The Tru-Traffic^{TM} comparison (before retiming/after implementation) reports for the weekday morning, mid-day and evening, as well as Saturday peak hours are presented in **Appendix A**.



Table 1 Before Retiming/After Implementation Results for Coordinated Segment of Sweetbriar Avenue/Sloan Avenue (Whitehead Road to Klockner Road)--Hamilton Township, Mercer County

Time Period	Travel '	Time (% Dif	ference)	Cumulative Delay (% Difference)				
	EB	WB	Combined	EB	WB	Combined		
Weekday AM	-3%	-28%	-17%	-8%	-61%	-47%		
Weekday Mid-Day	-13%	-28%	-22%	-87%	-97%	-94%		
Weekday PM	-15%	-33%	-25%	-57%	-95%	-85%		
Saturday Mid-Day	-24%	-30%	-27%	-84%	-87%	-85%		

C. Project Description

Sweetbriar Avenue/Sloan Avenue, Mercer County Route 649 is an urban minor arterial with a west to east orientation. Within the project area, the roadway is known as Sweetbriar Avenue to the west from Whitehead Road to American Metro Boulevard. From American Metro Boulevard to the east, the roadway is known as Sloan Avenue. The corridor project limits extend 1.17 miles along County Route 649 (Sweetbriar Avenue/Sloan Avenue) from Whitehead Road (CR 616) at the western limit to Klockner Road at the eastern limit.

The entire project corridor is in Hamilton Township, Mercer County. US Route 1 is easily accessible from the west end of Sweetbriar Road, north along Whitehead Road, with ramp access less than 0.20 miles to the north. Interstate 295 is accessible to the east end of the corridor from Sloan Avenue. The I-295 interchange is a full cloverleaf configuration with access to north and south I-295.

Land use along Mercer County Route 649 is a mixture of land uses, including a major transit station, industrial, residential and office complexes. The Ewing Lawrence Sewerage Authority is positioned on the west end to the north along Whitehead Road. Industrial manufacturing facilities are located to the west, and south along Whitehead Road. The western half mile stretch of Sweetbriar Avenue runs parallel to Assunpink Creek and remains undeveloped. Residential development is located on the northside of the corridor in the vicinity of Vetterlein Avenue. American Metro Boulevard provides access to medical facilities, commercial office space and the condominium complex, The Crossings at Hamilton Station.

At the east end of the corridor, the Hamilton Train Station is accessible from a signalized intersection with Klockner Road. The entrance to the train station is via the north approach leg of the signalized intersection. The Hamilton Train Station provides access to AMTRAK's Northeast Corridor and its regional destinations including New York City, Penn Station, as well as Philadelphia, 30th Street Station. Many commuters utilize the trains on a daily basis, including weekends, accessing the train station facility from I-295 from the east or Route 1 from the west.

Within the project limits, four (4) signalized intersections exist. The following is a list of signalized intersections within the project limits:

- 1. Sweetbriar Avenue (CR 649) & Whitehead Road (CR 616) [MP 0]
- 2. Sweetbriar Avenue (CR 649) & Vetterlein Avenue [MP 0.65]
- 3. Sweetbriar Avenue/Sloan Avenue (CR 649) & American Metro Boulevard [MP 0.93]
- 4. Sloan Avenue (CR 649) & Klockner Road/NJ Transit Hamilton Train Station [MP 1.17]

The project corridor location is shown in **Exhibit 1**.




Exhibit 1 - Project Corridor Location and Intersections



LOCATION MAP

DVRPC NEW JERSEY SIGNAL TIMING INITIATIVE CR 649 - SWEET BRIAR AVENUE AND SLOAN AVENUE HAMILTON TOWNSHIP, MERCER COUNTY









All four intersections are included in the retiming work effort. Each of the four project intersections have an electrical plan and layout plan, issued by Mercer County Engineering Department. The existing day plan schedule for the project intersections was straightforward: the four signals under Mercer County jurisdiction operated with a single "free" plan 24 hours a day, 7 days per week. The existing timing directives for each intersection are shown in **Appendix B**.

II. Data Collection

A. Turning Movement Counts

Peak hour intersection counts were conducted at the project intersections during the weekday morning (6:30 AM to 9:30 AM), weekday mid-day (11:30 AM to 2:30 PM) and weekday evening (3:00 PM to 7:00 PM) peak hour periods. Saturday counts were taken between 10:00 AM and 4:00 PM. The manual turning movement counts (TMCs) were taken on Saturday, October 2, 2021 and Tuesday, October 5, 2021 by the TWT team. The TMCs are available on the project website, http://www.dvrpc.taylorwiseman.com/.

B. Automatic Traffic Recorder (ATR) Counts

In October 2021, automatic traffic recorder counts were taken by the TWT team as presented in Table 2:

Table 2 2021 Average Daily Traffic Sweetbriar Avenue/Sloan Avenue

Location	Average Daily Traffic
Sweetbriar Avenue, west of Rutgers Avenue – WB Traffic	7,771 vehicles
Sweetbriar Avenue, west of Rutgers Avenue – EB Traffic	8,199 vehicles
Total ADT	15,970 vehicles
Sweetbriar Avenue, west of Sandalwood Avenue – WB Traffic	7,832 vehicles
Sweetbriar Avenue, west of Sandalwood Avenue – EB Traffic	8,239 vehicles
Total ADT	16,071 vehicles
Sloan Avenue, west of Klockner Road – WB Traffic	9,162 vehicles
Sloan Avenue, west of Klockner Road – EB Traffic	10,078 vehicles
Total ADT	19,240 vehicles

The twenty-four hour counts clearly show the fluctuation of traffic volumes the project corridor experiences on any given day. The western segment (west of American Metro Boulevard) of the corridor experiences almost twenty percent less traffic than the eastern section of the corridor. The automatic traffic recorder counts are available on the project website: http://dvrpc.taylorwiseman.com/.





C. Travel Time Runs

Travel time runs were collected within the project area both before and after initial timing plan implementation. Using a GPS enabled laptop and the software Tru-TrafficTM, trip logs were recorded along eastbound and westbound Sweetbriar Avenue/Sloan Avenue. Tru-TrafficTM was also utilized during implementation to fine-tune splits and offsets.

D. Traffic Signal Timing and Phasing Data

Traffic signal timing and phasing data were obtained from the Mercer County Engineering Office for the project corridor. The existing timing directives are presented in **Appendix B**. Movement, sequence, and timing information, as well as various controller settings and time of day/date were field verified. The controller units were set to universal time utilizing smart phone applications and time variances were noted.

E. Field Review of Existing Operations

Field notes were collected at each of the locations on various intersection, signal, and traffic characteristics to assist in model development and signal optimization. Information gathered included lane geometry,

storage lengths, number and types of signal heads, cabinet and pedestrian push button locations, and signal phasing.

Posted speed limits, left turn types (protected, protected/permitted, or permitted), turn restrictions, and the presence of roadway lighting and signal back plates were noted. Vehicle detection was observed for proper operation, both on the street and in the cabinet. Pedestrian push buttons were tested for proper operation during the field review. Any other unique characteristics were also recorded.

All corridor controllers are Econolite ASC/3-2100, in a NEMA TS-1 configuration. All detection on the



Photo 2: Controller at Sweetbriar Avenue & Vetterlein Avenue. Note evidence of insect infestation.

corridor was functioning at the end of implementation. The controller cabinets, in general, were in poor condition. The controllers at Vetterlein Avenue, American Metro Boulevard and Hamilton Train Station/Klockner Road had notable snake, rodent and insect infestations. The presence of these intruders will likely impact the reliability of the traffic signals, as well as the health/safety of maintenance technicians accessing the controller assemblies.





III. Analysis and Implementation

A. Modeling

The TWT team developed a set of base SynchroTM models for management of the new traffic data, initial analysis of the intersection with and without various timing changes and a screening level review of each intersection's overall potential for capacity-level improvements using the Intersection Capacity Utilization (ICU) Methodology. Microscopic simulation using SimTrafficTM was used to assess the impact of unmet demand, turn pocket overflow, metering and spillback, and the effects of origin-destination pairs. Tru-TrafficTM was used to assist in offset determination in order to assess early release issues created when minor phases gap out and unused cycle time is typically sent back to the coordinated phases.

It is important to note that the delay minimization focus of the optimization routine in SynchroTM is helpful to a point in deriving improved cycle lengths and splits; however, this method does not necessarily favor corridor progression and bandwidth requirements. After development of the base models and supplemental evaluations in SimTrafficTM, the UTDF file transfer feature with various spreadsheets was used to create base Tru-TrafficTM models for more in-depth optimization. Synchro summary reports are available on the project website: http://dvrpc.taylorwiseman.com/.

B. Implementation

During the week of March 14, 2022, the consultant team implemented the optimized timing plans into the Sweetbriar Avenue/Sloan Avenue project controllers (Whitehead Road to Klockner Road). The TWT team verified that each controller maintained a common time standard.

The traffic characteristics of this corridor are bifurcated as Vetterlein Avenue and Whitehead Road do not experience the traffic associated with the office complex at American Metro Boulevard or the transit-oriented trips at the NJ Transit Hamilton Rail Station. It was apparent that keeping the entire corridor in coordinated operation during off-peak times was counterproductive, as local delays experienced at the western signals were excessive. Accordingly, the two western signals (Vetterlein, Whitehead) are not in coordinated operation during some of the weekday off-peak.

The four signalized intersections on Mercer County Route 649 all operate in coordination via time base during peak commuter hours. There are no GPS units to keep the clocks in sync; and significant "drifting" of the common time-standard is expected. The time keeping function of the coordination unit is based on the 60 Hz line frequency of the utility serving the intersection. If the power is interrupted, or the line frequency varies to controllers utilizing Time Based Coordination, the internal controller clock relies on a battery which will result in time variations. The TWT team has inspected the corridor controllers for inconsistent drift and have found that drift is in fact occurring. This drift was expected and does impact the effectiveness of the coordinated timing plan on the corridor. Given the overall "poor" condition of the controller assemblies on the corridor, Mercer County should consider installation of GPS pucks and mitigation of the insect/snake/rodent infestations. In the interim, Mercer County should consider inspection of controller clocks at least once a month, resetting them to universal time as necessary.

_

¹ The controller at Sweetbriar Avenue and Vetterlein Avenue was inspected by the TWT team on Thursday, April 28, 2022 and the internal time clock had varied + 9 seconds from Naval Observatory time. Time variances such as these will sabotage the effectiveness of the coordinated timing plans on the CR 649 corridor.





In addition to the general concerns about the common time standard and the integrity of the controller cabinets, the TWT team identified the following specific concerns:

Whitehead Road (CR 616):

- Pedestrian pushbutton on the southeast corner for NB pedestrian movement (Ø4) does not place a call in the controller.
- Pedestrian display on northeast corner for pedestrian phase 8 (WB) not displaying countdown.

<u>Vetterlein Avenue:</u>

- Detection for side street (SB) was inconsistent. Numerous false calls were observed during field view and implementation.
- Controller assembly had snake, spider and insect infestations which may impact reliability of the controller assembly.

American Metro Boulevard:

- Ø1, the eastbound CR 649 left-turn phase, has a constant call on video detection.
- Pedestrian button on the northwest corner for pedestrian Ø4 (southbound) does not place call in controller
- UPS in cabinet not functioning and has been turned off.





Photo 3: Insect infestation at Vetterlein Avenue (April, 2022)

• Rodents (Rats) were in cabinet during implementation. It is recommended that the nest be cleared from the controller assembly.

NI Transit Hamilton Rail Station/Klockner Road:

- Pedestrian pushbutton missing on southwest corner for pedestrian Ø8 (southbound).
- Rodents were in cabinet during implementation. It is recommended that the nest be cleared from the controller assembly.

On the project, corridor coordinated operation was installed during the week from 6:30 AM to 7:30 PM, and from 8:00 AM to 8:00 PM on the weekend. The weekday programs include an AM, Mid-Day, PM and PM Off-Peak. The weekend program has a single coordinated timing plan. Cycle lengths on Mercer County Route 649 vary between 70 and 90 seconds throughout the AM, Midday, PM, PM off-peak and weekends. The corridor was observed during all (AM, Mid-Day, PM, PM Off-Peak, and weekend) timing plans. Minor changes were made to offset, split and cycle as necessary and were documented so that the final timing directives would reflect field conditions. A detailed summary of the implementing timing process is provided in **Appendix C**.





C. Fine-Tuning of Signal Timings

The TWT team observed each new timing plan at every intersection during its respective peak hour to



Photo 4: Looking WB from CR 649 at Whitehead Road (CR 616)

ensure each phase split was appropriate for the traffic conditions present. If a movement or intersection was over capacity, split adjustments were made to manage queue spillback and blockage.

In addition to fine-tuning splits, offset adjustments often have a larger effect on the performance of the corridor. Offsets were adjusted at the coordinated intersections by conducting field observations along the corridor. During implementation, the TWT team utilized Tru-Traffic ™ in conjunction with a direct connect GPS unit to observe the operation of the progressive

system. TWT team engineers can track the system time as well as their location within the time-space diagram for any time period. This effort results in several minor adjustments to split and offset times during a time period.

The revised signal timings are available from the project website, http://www.dvrpc.taylorwiseman.com. Updated signal timing directives were developed by the consultant team, with electronic and paper copies delivered to Mercer County and laminated copies placed in each controller.

IV. Results

A. Before and After Data

Travel time data along the corridor was collected before and after implementation of the initial timing plans during the weekday morning, mid-day, evening and the weekend mid-day peak hour periods.

With implementation of the new timing plans and maintenance of a uniform time clock between controllers, progression along Sweetbriar Avenue/Sloan Avenue (CR 649) between Whitehead Road and Klockner Road Avenue improved significantly, in both directions. For all four peak hour periods, the implemented retiming is producing positive results and significant savings in travel time, delay, the number of stops, and travel speed in both directions. Refer to **Appendix A** for the travel time summary reports for the time periods. **Table 3** summarizes both the directional and cumulative summary of performance metrics collected on Sweetbriar Avenue/Sloan Avenue (CR 649).





Table 3

Coordinated Segment of Sweetbriar Avenue/Sloan Avenue (CR 649) (Whitehead Road to Klockner Road) Hamilton Township, Mercer County Peak Hour Travel Time and Delay Comparison based on Travel Time Runs completed with Tru-Traffic 10.0*

		AM Peak		Mid-da	y Peak	PM I	eak	Weekend Mid-day Peak	
	Direction	Travel Time (s)	Delay (s)	Travel Time (s)	Delay (s)	Travel Time (s)	Delay (s)	Travel Time (s)	Delay (s)
73	Existing	133	16	132	16	144	24	146	23
Eastbound	Implemented	129	15	115	2	123	10	111	4
astb	Difference	-4	-1	-17	-14	-21	-13	-35	-19
ш	% Difference	-3%	-8%	-13%	-87%	-15%	-57%	-24%	-84%
р	Existing	195	64	160	39	173	50	159	28
Westbound	Implemented	141	25	116	1	117	3	111	4
/estk	Difference	-54	-39	-45	-38	-57	-47	-47	-25
>	% Difference	-28%	-61%	-28%	-97%	-33%	-95%	-30%	-87%
ns	Existing	164	40	147	28	159	37	152	26
ectio	Implemented	137	21	115	2	119	5	111	4
Both Directions	Difference	-28	-19	-32	-27	-40	-32	-41	-22
Bot	% Difference	-17%	-47%	-22%	-94%	-25%	-85%	-27%	-85%

Eastbound: Whitehead Road to Klockner Road Westbound: Klockner Road to Whitehead Road


B. Opportunities for Improvement

Sweetbriar Avenue/Sloan Avenue, Mercer County Route 649, had basic timing in place at the start of the project. As identified previously in the report, there are potential challenges to the sustainability of the updated timing on this corridor. The condition of the controllers on this corridor is a concern, as at least three of the controller assemblies have major rodent/insect/snake infestations. None of the controllers have GPS pucks installed, and the TWT team has already verified that the controller time clocks will drift every day which will impact the efficiency of the signal timing.

The Regional Traffic Signal Timing Initiative has shown that significant improvement in traffic operations is possible with the introduction of new timing plans as well as a common time standard on the Sweetbriar Avenue/Sloan Avenue (Mercer County Route 649) corridor. The consultant team recommends the following:

^{*}Values as reported in Tru-Traffic summary report. Rounding errors possible.







- 1. Regular surveillance and adjustment of controller clock time to ensure the individual controllers maintain a common time standard. Installation of GPS units in the cabinets would alleviate this need. Initially, we would recommend surveillance every 30-days adjusting the frequency based on the time drift observed.
- 2. Focus on maintenance of the traffic signal installations immediately. Identify and correct missing or malfunctioning vehicular and pedestrian detection on the corridor.
- 3. Clean or replace the controller cabinets on the corridor. Take preventative action to avoid snake, rodent and insect infestations.
- 4. Timing plans on the corridor should be revisited within 3-5 years.
- 5. Mercer County should consider use of a GPS unit in all future cabinets, ensuring that the controller time clocks are synchronized with atomic time daily.

C. Additional Resources/Project Data

Additional information, including project data, analysis files, and other detailed reports will be available on the project website at: http://www.dvrpc.taylorwiseman.com/

Appendix A

Travel Time & Delay Report for Sweet Briar Ave (CR 649) - AM Peak

Legend:

CTT:

Summarized Cumulative Travel Time since beginning of Run (seconds)

CPLSD:

Summarized Cumulative Posted Speed Limit Delay since beginning of Run (seconds)

CPLRT:

Summarized Cumulative Posted Speed Limit Running Time, or Travel Time since beginning of Run if maintaining Posted Speed Limit (seconds) = accumulation of DL/PLS since beginning of Run

CStopD:

Summarized Cumulative Stopped Delay since beginning of Run (seconds). The "Stopped Delay" is counted from when the speed drops below 5 mph after exceeding 15 mph until it exceeds 15 mph once again

Summarized Cumulative Actual Average Speed since beginning of Run (mph) = CTL/CTT

Summarized Cumulative number of Stops in Run. A "Stop" is counted when the speed drops below 5 mph after exceeding 15 mph TV-

Summarized Through Volume (vph)

CPUFC:

Summarized Cumulative Fuel Consumption, from Penic & Upchurch model with TRANSYT7F-10 default coefficients (gal/hr) (= Cumulative (TU5280*10.51242*exp(0.024609*DS)DS) + Delay/3600*(0.0468) + Stops*(3.8424*DS^1.657 + 1.681*DS^1.48922)/1.0E5)*TV) CUFCOF:

Summarized Cumulative Carbon Monoxide Emissions using Synchro 7 formula (from unpublished Oak Ridge National Labs letter to Federal Highway Administration) and University of Florida model for Fuel Consumption (g/hr) (= Cumulative UFFC*69.9)

Cumulative Summary of runs Eastbound from Whitehead Rd (CR 616) (#1)
7 Before-type runs, 7 of unverifiable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during 7:0 9 After-type runs 5 of unverifiable grigin, collected Wednesday 03/16/22 to Wednesday 03/3/22 over day(s) Wed, with starting times duri

	CTT	CPLSD	CPLRT	CStopD	CAS	CStops	TV	CPUFC	CUFCOE
to NJ Tra	nsit Ha	milton Rail	Station (#-	4)					
Average Before (n=7)	133	27	106	16	32.6	0.6	610	34.8	2450.3
Std Dev Before (n=7)	22	22	0	19	5.1	0.5	610	7.7	422.8
Average After (n=9)	129	23	106	15	33.1	0.8	610	36.9	2464.1
Std Dev After (n=9)	13	13	0	13	3.5	0.7	610	8.9	382.6
Difference	-4	-4	0	-1	0.5	0.2	610	2.1	13.8
Std Dev Difference	26	26	0	23	6.2	0.9	610	11.8	570.2
% Difference	-3%	-17%	0%	-8%	1.60%	36.10%	610	6.10%	0.60%

Cumulative Summary of runs Westbound from NJ Transit Hamilton Rail Station (#4)

7 Before-type runs, 7 of unverifiable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during 7:0

	CTT	CPLSD	CPLRT	CStopD	CAS	CStops	TV	CPUFC	CUFCOE
to Whitel	nead Ro	I (CR 616) (#1)						
Average Before (n=7)	195	91	104	64	22.9	1.9	0	22.6	1520.3
Std Dev Before (n=7)	31	31	0	28	3.5	1.5	0	13.5	545.4
Average After (n=15)	141	37	104	25	30.9	0.7	0	12.3	941.6
Std Dev After (n=15)	28	28	0	26	5.2	0.5	0	0.1	79.7
Difference	-54	-54	0	-39	8	-1.2	0	-10.3	-578.7
Std Dev Difference	42	42	0	39	6.3	1.5	0	13.5	551.2
% Difference	-28%	-59%	0%	-61%	34.80%	-64.10%	0	-45.50%	-38.10%

Cumulative Summary of all runs, either direction through artery

14 Before-type runs, 14 of unverifiable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during i 24 After-type runs, 14 of unverifiable origin, collected Wednesday 03/16/22 to Wednesday 03/23/22, over day(s) Wed, with starting times d

	CTT	CPLSD	CPLRT	CStopD	CAS	CStops	TV	CPUFC	CUFCOE
to End of	Artery								
Average Before (n=14)	164	59	105	40	27.8	1.2	610	28.7	1985.3
Std Dev Before (n=14)	41	42	1	34	6.6	1.3	610	12.3	672.8
Average After (n=24)	137	32	105	21	31.7	0.7	610	21.5	1512.5
Std Dev After (n=24)	24	24	1	22	4.7	0.6	610	13.3	788.5
Difference	-28	-27	0	-19	4	-0.5	610	-7.2	-472.8
Std Dev Difference	47	48	2	40	8	1.4	610	18.1	1036.5
% Difference	-17%	-46%	0%	-47%	14.30%	-41.70%	610	-24.90%	-23.80%

Summary of runs Eastbound from Whitehead Rd (CR 616) (#1)

9 After-type runs, 5 of unverifiable origin, collected Wednesday 03/16/22 to Wednesday 03/23/22, over day(s) Wed, with starting times during 6:57:40 AM to 8:54:26 A

										0	
Node	CTT	DL	CPLSD	CPLRT	CStopD	CAS	PLS	CStops	TV	CPUFC	CUFCOE
to Vetterle	ein Ave (#	2)									

Average Before (n=7)	71	3471	11	59	7	35.8	40	0.1	675	17.4	1291.4
Std Dev Before (n=7)	23	0	23	0	19	7.5	o	0.4	675	5.7	398.7
Average After (n=9)	62	3471	3	59	0	38.1	40	0	675	15.3	1142
Std Dev After (n=9)	3	0	3	0	0	1.7	o	o	675	0.1	29.7
Difference	-8	0	-8	0	-7	2.3	0	-0.1	675	-2.2	-149.4
Std Dev Difference	23	0	23	0	19	7.7	0	0.4	675	5.7	399.8
% Difference	-12%	0%	-72%	0%	-100%	6.40%	0%	-100.00%	675	-12.60%	-11.60%
to Americ	an Metro I	Blvd (#3)									
Average Before (n=7)	102	1507	17	85	12	34.1	40	0.4	656	27.9	1939.6
Std Dev Before (n=7)	21	0	21	0	19	5.3	o	0.5	656	7.8	412.2
Average After (n=9)	91	1507	6	85	1	37.1	40	0.1	656	23.1	1677.7
Std Dev After (n=9)	8	0	8	0	4	3.1	o	0.3	656	4.7	218.2
Difference	-11	0	-11	0	-11	3.1	0	-0.3	656	-4.8	-261.9
Std Dev Difference	23	0	23	0	19	6.2	0	0.6	656	9.1	466.4
% Difference	-11%	0%	-63%	0%	-89%	9.00%	0%	-74.10%	656	-17.20%	-13.50%
to NJ Tra	nsit Hamil	ton Rail St	tation (#4)								
Average Before (n=7)	133	1257	27	106	16	32.6	40	0.6	610	34.8	2450.3
Std Dev Before (n=7)	22	0	22	0	19	5.1	o	0.5	610	7.7	422.8
Average After (n=9)	129	1257	23	106	15	33.1	40	0.8	610	36.9	2464.1
Std Dev After (n=9)	13	o	13	0	13	3.5	o	0.7	610	8.9	382.6
Difference	-4	0	-4	0	-1	0.5	0	0.2	610	2.1	13.8
Std Dev Difference	26	0	26	0	23	6.2	0	0.9	610	11.8	570.2
% Difference	-3%	0%	-17%	0%	-8%	1.60%	0%	36.10%	610	6.10%	0.60%

Summary of runs Westbound from NJ Transit Hamilton Rail Station (#4)
7 8efore-type runs, 7 of unverifiable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during 7:01:42 AM to 8:43:38 AM
15 After-type runs, 9 of unverifiable origin, collected Wednesday 03/15/22 to Wednesday 03/23/22, over day(s) Wed, with starting times during 6:44:17 AM to 8:50:23/
Node CTT DL CPLSD CPRT CStopp CAS PLS CStops TV CPUFC CUFCOE

Node	CTT	DL	CPLSD	CPLRT	CStopD	CAS	PLS	CStops	TV	CPUFC	CUFCOE
to Americ	an Metro	Blvd (#3)									
Average Before (n=7)	44	1257	25	19	9	21.5	45	0.4	702	14	930
Std Dev Before (n=7)	12	0	12	0	13	5.8	0	0.5	702	9.9	421.1
Average After (n=15)	24	1257	5	19	0	36.8	45	0	702	5.9	459.3
Std Dev After (n=15)	4	o	4	o	o	5.8	0	o	702	o	42.8
Difference	-20	0	-20	0	-9	15.3	0	-0.4	702	-8.1	-470.8
Std Dev Difference	13	0	13	0	13	8.2	0	0.5	702	9.9	423.2
% Difference	-45%	0%	-79%	0%	-100%	71.40%	0%	-100.00%	702	-58.00%	-50.60%
to Vetterl	ein Ave (#	¥2)	1	1	1			1	1	1	1
Average Before (n=7)	76	1507	31	45	9	25.5	40	0.6	673	22.6	1520.3
Std Dev Before (n=7)	13	0	13	0	13	4.1	0	0.8	673	13.5	545.4
Average After (n=15)	52	1507	7	45	0	36.8	40	0	673	12.3	941.6
Std Dev After (n=15)	8	0	8	0	0	5.3	0	o	673	0.1	79.7
Difference	-24	0	-24	0	-9	11.3	0	-0.6	673	-10.3	-578.7
Std Dev Difference	15	0	15	0	13	6.7	0	0.8	673	13.5	551.2
% Difference	-32%	0%	-78%	0%	-100%	44.20%	0%	-100.00%	673	-45.50%	-38.10%
	ead Rd (CR 616) (#	1)					•	•	•	•
Average Before (n=7)	195	3471	91	104	64	22.9	40	1.9	0	22.6	1520.3
Std Dev Before (n=7)	31	0	31	0	28	3.5	0	1.5	0	13.5	545.4
Average After (n=15)	141	3471	37	104	25	30.9	40	0.7	0	12.3	941.6
Std Dev After (n=15)	28	0	28	0	26	5.2	0	0.5	0	0.1	79.7
Difference	-54	0	-54	0	-39	8	0	-1.2	0	-10.3	-578.7
Std Dev Difference	42	0	42	0	39	6.3	0	1.5	0	13.5	551.2
% Difference	-28%	0%	-59%	0%	-61%	34.80%	0%	-64.10%	0	-45.50%	-38.10%

Travel Time & Delay Report for Sweet Briar Ave (CR 649) - MD Peak

Legend:

CTT:

Summarized Cumulative Travel Time since beginning of Run (seconds)

CPI SD:

Summarized Cumulative Posted Speed Limit Delay since beginning of Run (seconds)

CPLRT:

Summarized Cumulative Posted Speed Limit Running Time, or Travel Time since beginning of Run if maintaining Posted Speed Limit (seconds) = accumulation of DL/PLS since beginning of Run

Summarized Cumulative Stopped Delay since beginning of Run (seconds). The *Stopped Delay* is counted from when the speed drops below 5 mph after exceeding 15 mph until it exceeds 15 mph once again

Summarized Cumulative Actual Average Speed since beginning of Run (mph) = CTL/CTT

CStops:

Summarized Cumulative number of Stops in Run. A "Stop" is counted when the speed drops below 5 mph after exceeding 15 mph

Summarized Through Volume (vph)

CPUFC:

Summarized Cumulative Fuel Consumption, from Penic & Upchurch model with TRANSYT7F-10 default coefficients (gal/hr) (= Cumulative (TL/5280*(0.51242*exp(0.024609*DS)/DS) + Delay/3800*(0.0468) + Stops*(3.8424*DS*1.657 + 1.681*DS*1.48922)/1.0E5)*TV) CUFCOE:

Summarized Cumulative Carbon Monoxide Emissions using Synchro 7 formula (from unpublished Oak Ridge National Labs letter to Federal Highway Administration) and University of Florida model for Fuel Consumption (g/hr) (= Cumulative UFFC*69.9)

Cumulative Summary of runs Eastbound from Whitehead Rd (CR 616) (#1)

7 Before-type runs, 7 of unverifiable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during 11:0: 9 After-type runs, 9 of unverifiable origin, collected Wednesday 03/23/22 to Wednesday 03/23/22, over day(s) Wed, with starting times during

	CTT	CPLSD	CPLRT	CStopD	CAS	CStops	TV	CPUFC	CUFCOE
to NJ Tra	nsit Ha	milton Rail	Station (#	4)					
Average Before (n=7)	132	26	106	16	32.2	0.7	405	26	1771
Std Dev Before (n=7)	9	9	0	14	2.3	0.5	405	4.8	203.9
Average After (n=9)	115	8	106	2	37	0.2	405	21.5	1524.3
Std Dev After (n=9)	9	9	0	4	2.8	0.4	405	4.7	194.6
Difference	-17	-17	0	-14	4.8	-0.5	405	-4.5	-246.7
Std Dev Difference	12	12	0	15	3.6	0.7	405	6.7	281.8
% Difference	-13%	-67%	0%	-87%	14.90%	-68.90%	405	-17.40%	-13.90%

Cumulative Summary of runs Westbound from NJ Transit Hamilton Rail Station (#4)

8 Before-type runs, 8 of unverifiable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during 10:5l 11 After-type runs, 11 of unverifiable origin, collected Wednesday 03/23/22 to Wednesday 03/23/22, over day(s) Wed, with starting times du

	CTT	CPLSD	CPLRT	CStopD	CAS	CStops	TV	CPUFC	CUFCOE
to Whiteh	ead Ro	(CR 616) (#	‡1)						
Average Before (n=8)	160	56	104	39	27.1	1.1	0	10.5	724.7
Std Dev Before (n=8)	22	22	0	22	3.8	0.6	0	4.9	242.5
Average After (n=11)	116	12	104	1	36.6	0.1	0	7.8	594.9
Std Dev After (n=11)	9	9	0	4	2.8	0.3	0	0.1	56.3
Difference	-45	-45	0	-38	9.5	-1	0	-2.7	-129.8
Std Dev Difference	24	24	0	22	4.7	0.7	0	4.9	248.9
% Difference	-28%	-79%	0%	-97%	35.10%	-91.90%	0	-25.40%	-17.90%

Cumulative Summary of all runs, either direction through artery

15 Before-type runs, 15 of unverifiable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during 10

20 Arter-type runs, 20 or unvermable origin, collected wednesday 05/25/22 to wednesday 05/25/22, over day(s) wed, with starting times of										
	CTT	CPLSD	CPLRT	CStopD	CAS	CStops	TV	CPUFC	CUFCOE	
to End of	Artery									
Average Before (n=15)	147	42	105	28	29.5	0.9	405	17.7	1213	
Std Dev Before (n=15)	22	23	1	22	4	0.6	405	9.3	582.3	
Average After (n=20)	115	10	105	2	36.8	0.1	405	13.9	1013.1	
Std Dev After (n=20)	9	9	1	4	2.8	0.4	405	7.6	492.6	
Difference	-32	-32	0	-27	7.3	-0.8	405	-3.8	-199.8	
Std Dev Difference	24	25	2	22	4.9	0.7	405	12	762.7	
% Difference	-22%	-76%	0%	-94%	24.80%	-83.90%	405	-21.20%	-16.50%	

Summary of runs Eastbound from Whitehead Rd (CR 616) (#1)

7 Before-type runs, 7 of unwerflable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during 11:03:49 AM to 12:40:43 PM

9 After-type runs, 9 of unwerflable origin, collected Wednesday 03/23/22 to Wednesday 03/23/22, over day(s) Wed, with starting times during 11:05:48 AM to 12:57:58 P

Node	CTT	DL	CPLSD	CPLRT	CStopD	CAS	PLS	CStops	TV	CPUFC	CUFCOE
to Vetterl	ein Ave (
Average Before (n=7)	62	3471	3	59	0	38.2	40	0	488	11	824.7
Std Dev Before (n=7)	4	0	4	o	0	2.6	o	0	488	0.1	29.5
Average After (n=9)	60	3471	0	59	0	39.8	40	0	488	11	804.9
Std Dev After (n=9)	3	o	3	o	o	1.9	0	o	488	0	20.2
Difference	-3	0	-3	0	0	1.5	0	0	488	0	-19.8
Std Dev Difference	5	0	5	0	o	3.2	0	o	488	0.1	35.8
% Difference	-4%	0%	-87%	0%	N/D	4.00%	0%	N/D	488	-0.30%	-2.40%
to Americ	can Metro	Blvd (#3)									
Average Before (n=7)	95	1507	10	85	5	36.1	40	0.3	497	18.9	1321
Std Dev Before (n=7)	14	0	14	o	9	4.8	o	0.5	497	5.3	263.4
Average After (n=9)	92	1507	7	85	2	36.7	40	0.2	497	18.1	1274.7
Std Dev After (n=9)	7	0	7	o	4	3	o	0.4	497	4.7	184.7
Difference	-3	0	-3	0	-3	0.7	0	-0.1	497	-0.7	-46.3
Std Dev Difference	16	0	16	0	10	5.7	0	0.7	497	7.1	321.7
% Difference	-3%	0%	-30%	0%	-62%	1.80%	0%	-22.20%	497	-3.90%	-3.50%
to NJ Tra	nsit Ham	ilton Rail S	tation (#4))							
Average Before (n=7)	132	1257	26	106	16	32.2	40	0.7	405	26	1771
Std Dev Before (n=7)	9	0	9	o	14	2.3	o	0.5	405	4.8	203.9
Average After (n=9)	115	1257	8	106	2	37	40	0.2	405	21.5	1524.3
Std Dev After (n=9)	9	0	9	o	4	2.8	o	0.4	405	4.7	194.6
Difference	-17	0	-17	0	-14	4.8	0	-0.5	405	-4.5	-246.7
Std Dev Difference	12	0	12	0	15	3.6	0	0.7	405	6.7	281.8
% Difference	-13%	0%	-67%	0%	-87%	14.90%	0%	-68.90%	405	-17.40%	-13.90%

Summary of runs Westbound from NJ Transit Hamilton Rail Station (#4)

8 Before-type runs, 8 of unverifiable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during 10:58:47 AM to 12:47:01 PM

11 After-type runs, 11 of unverifiable origin, collected Wednesday 03/23/22 to Wednesday 03/23/22, over day(s) Wed, with starting times during 11:02:04 AM to 12:54:01

Node	CTT	DL	CPLSD	CPLRT	CStopD	CAS	PLS	CStops	TV	CPUFC	CUFCOE
	an Metr	o Blvd (#3	3)								
Average			,	1							
Before (n=8)	30	1257	11	19	4	32.6	45	0.1	436	5.1	371.2
Std Dev Before (n=8)	14	0	14	o	12	8.7	0	0.4	436	4.1	218.9
Average After (n=11)	23	1257	4	19	0	37.9	45	0	436	3.7	279.3
Std Dev After (n=11)	4	0	4	0	0	4.4	0	0	436	0	22.4
Difference	-7	0	-7	0	-4	5.3	0	-0.1	436	-1.5	-91.8
Std Dev Difference	14	o	14	o	12	9.7	0	0.4	436	4.1	220
% Difference	-23%	0%	-61%	0%	-100%	16.30%	0%	-100.00%	436	-28.90%	-24.70%
to Vetterl	ein Ave	(#2)									
Average Before (n=8)	58	1507	13	45	5	33.6	40	0.3	436	10.5	724.7
Std Dev Before (n=8)	15	0	15	0	12	6.3	0	0.5	436	4.9	242.5
Average After (n=11)	51	1507	7	45	0	37.2	40	0	436	7.8	594.9
Std Dev After (n=11)	9	o	9	o	o	5	0	0	436	0.1	56.3
Difference	-7	0	-7	0	-5	3.6	0	-0.3	436	-2.7	-129.8
Std Dev Difference	17	0	17	0	12	8.1	0	0.5	436	4.9	248.9
% Difference	-12%	0%	-51%	0%	-100%	10.70%	0%	-100.00%	436	-25.40%	-17.90%
to Whiteh	ead Rd	(CR 616) (#1)								
Average Before (n=8)	160	3471	56	104	39	27.1	40	1.1	0	10.5	724.7
Std Dev Before (n=8)	22	0	22	0	22	3.8	0	0.6	0	4.9	242.5
Average After (n=11)	116	3471	12	104	1	36.6	40	0.1	0	7.8	594.9
Std Dev After (n=11)	9	0	9	o	4	2.8	0	0.3	0	0.1	56.3
Difference	-45	0	-45	0	-38	9.5	0	-1	0	-2.7	-129.8

Std Dev Difference	24	0	24	0	22	4.7	0	0.7	0	4.9	248.9
% Difference	-28%	0%	-79%	0%	-97%	35.10%	0%	-91.90%	0	-25.40%	-17.90%

Travel Time & Delay Report for Sweet Briar Ave (CR 649) - PM Peak

Legend:

CTT:

Summarized Cumulative Travel Time since beginning of Run (seconds)

CPI SD:

Summarized Cumulative Posted Speed Limit Delay since beginning of Run (seconds)

CPLRT:

Summarized Cumulative Posted Speed Limit Running Time, or Travel Time since beginning of Run if maintaining Posted Speed Limit (seconds) = accumulation of DL/PLS since beginning of Run

Summarized Cumulative Stopped Delay since beginning of Run (seconds). The *Stopped Delay* is counted from when the speed drops below 5 mph after exceeding 15 mph until it exceeds 15 mph once again

Summarized Cumulative Actual Average Speed since beginning of Run (mph) = CTL/CTT

CStops:

Summarized Cumulative number of Stops in Run. A "Stop" is counted when the speed drops below 5 mph after exceeding 15 mph

Summarized Through Volume (vph)

CPUFC:

Summarized Cumulative Fuel Consumption, from Penic & Upchurch model with TRANSYT7F-10 default coefficients (gal/hr) (= Cumulative (TL/5280*(0.51242*exp(0.024609*DS)/DS) + Delay/3800*(0.0468) + Stops*(3.8424*DS*1.657 + 1.681*DS*1.48922)/1.0E5)*TV) CUFCOE:

Summarized Cumulative Carbon Monoxide Emissions using Synchro 7 formula (from unpublished Oak Ridge National Labs letter to Federal Highway Administration) and University of Florida model for Fuel Consumption (g/hr) (= Cumulative UFFC*69.9)

Cumulative Summary of runs Eastbound from Whitehead Rd (CR 616) (#1)

12 Before-type runs, 12 of unverifiable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during 3:1 8 After-type runs, 7 of unverifiable origin, collected Tuesday 03/15/22 to Wednesday 03/23/22, over day(s) Tue, Wed, with starting times dur

	CTT	CPLSD	CPLRT	CStopD	CAS	CStops	TV	CPUFC	CUFCOE
to NJ Tra	nsit Ha	milton Rail	Station (#	4)					
Average Before (n=12)	144	38	106	24	30.2	1.3	737	52.2	3365
Std Dev Before (n=12)	21	21	0	15	4.9	0.8	737	12.5	596.6
Average After (n=8)	123	17	106	10	34.6	0.6	737	42	2813.7
Std Dev After (n=8)	11	11	0	11	3.1	0.5	737	8.7	382.7
Difference	-21	-21	0	-13	4.4	-0.6	737	-10.2	-551.3
Std Dev Difference	24	24	0	18	5.8	0.9	737	15.2	708.7
% Difference	-15%	-56%	0%	-57%	14.60%	-50.00%	737	-19.50%	-16.40%

Cumulative Summary of runs Westbound from NJ Transit Hamilton Rail Station (#4)

13 Before-type runs, 13 of unverifiable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during 2: 14 After-type runs, 13 of unverifiable origin, collected Tuesday 03/15/22 to Wednesday 03/23/22, over day(s) Tue, Wed, with starting times d

	CTT	CPLSD	CPLRT	CStopD	CAS	CStops	TV	CPUFC	CUFCOE
to Whiteh	ead Ro	(CR 616) (#	¥1)						
Average Before (n=13)	173	70	104	50	25.7	1.5	0	21	1370.6
Std Dev Before (n=13)	29	29	0	26	4.4	0.7	o	10.8	509.1
Average After (n=14)	117	13	104	3	36.4	0.2	0	13	956.6
Std Dev After (n=14)	13	13	0	8	3.7	0.6	o	3.9	167.4
Difference	-57	-57	0	-47	10.7	-1.2	0	-8.1	-414.1
Std Dev Difference	32	32	0	27	5.8	0.9	0	11.5	535.9
% Difference	-33%	-81%	0%	-95%	41.60%	-85.30%	0	-38.30%	-30.20%

Cumulative Summary of all runs, either direction through artery
25 Before-type runs, 25 of unverifiable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during 3:1 22 After type runs, 20 of unverifiable origin, collected Tuesday 02/15/23 to Wednerday 02/22/23, over dayle) Tue, Wednerday 02/22/23

22 Aiter-type							over day(s) it		
	CTT	CPLSD	CPLRT	CStopD	CAS	CStops	TV	CPUFC	CUFCOE
to End of	Artery								
Average Before (n=25)	159	54	105	37	27.9	1.4	737	36	2327.9
Std Dev Before (n=25)	29	30	1	25	5.1	0.7	737	19.5	1151.9
Average After (n=22)	119	14	105	5	35.7	0.4	737	23.5	1631.9
Std Dev After (n=22)	13	12	1	10	3.5	0.6	737	15.4	949.9
Difference	-40	-40	0	-32	7.9	-1	737	-12.5	-696
Std Dev Difference	32	32	2	27	6.2	0.9	737	24.9	1493
% Difference	-25%	-74%	0%	-85%	28.30%	-73.30%	737	-34.60%	-29.90%

Summary of runs Eastbound from Whitehead Rd (CR 616) (#1)

12 Before-type runs, 12 of unverifiable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during 3:05:19 PM to 5:51:38 PM

8 After-type runs, 7 of unverifiable origin, collected Tuesday 03/15/22 to Wednesday 03/23/22, over day(s) Tue, Wed, with starting times during 2:43:09 PM to 5:54:35 PM

Node	CTT	<u>DL</u>	CPLSD	CPLRT	CStopD	CAS	PLS	CStops	TV	CPUFC	CUFCOE
to Vetter	lein Ave (#2)									
Average Before (n=12)	60	3471	1	59	0	39.9	40	0	799	18.1	1327.3
Std Dev Before (n=12)	3	o	3	o	0	1.9	o	0	799	0.1	39
Average After (n=8)	62	3471	3	59	0	38.1	40	0	799	18	1351.1
Std Dev After (n=8)	3	0	3	0	o	1.6	0	o	799	0.1	32.8
Difference	3	0	3	0	0	-1.8	0	0	799	0	23.8
Std Dev Difference	4	0	4	0	o	2.5	0	o	799	0.1	51
% Difference	4%	0%	426%	0%	N/D	-4.40%	0%	N/D	799	-0.20%	1.80%
to Ameri	can Metro	Blvd (#3)									
Average Before (n=12)	98	1507	13	85	6	35.3	40	0.4	775	32.5	2229.3
Std Dev Before (n=12)	18	0	18	0	9	5.3	0	0.5	775	8.8	449.8
Average After (n=8)	101	1507	16	85	10	33.6	40	0.6	775	35.9	2367.6
Std Dev After (n=8)	11	0	11	0	11	3.5	0	0.5	775	8.7	375.6
Difference	3	0	3	0	4	-1.7	0	0.2	775	3.4	138.3
Std Dev Difference	21	0	21	0	14	6.3	0	0.7	775	12.3	586
% Difference	3%	0%	23%	0%	69%	-4.80%	0%	50.00%	775	10.40%	6.20%
	ınsit Ham	ilton Rail S	Station (#4))							
Average Before (n=12)	144	1257	38	106	24	30.2	40	1.3	737	52.2	3365
Std Dev Before (n=12)	21	0	21	0	15	4.9	0	0.8	737	12.5	596.6
Average After (n=8)	123	1257	17	106	10	34.6	40	0.6	737	42	2813.7
Std Dev After (n=8)	11	0	11	0	11	3.1	0	0.5	737	8.7	382.7
Difference	-21	0	-21	0	-13	4.4	0	-0.6	737	-10.2	-551.3
Std Dev Difference	24	0	24	0	18	5.8	0	0.9	737	15.2	708.7
% Difference	-15%	0%	-56%	0%	-57%	14.60%	0%	-50.00%	737	-19.50%	-16.40%

Summary of runs Westbound from NJ Transit Hamilton Rail Station (#4)

13 Before-type runs, 13 of unverifiable origin, collected Tuesday 10/05/21 to Tuesday 10/05/21, over day(s) Tue, with starting times during 2:59:51 PM to 5:47:28 PM

14 After-type runs, 13 of unverifiable origin, collected Tuesday 03/15/22 to Wednesday 03/23/22, over day(s) Tue, Wed, with starting times during 3:02:38 PM to 5:50:30

Node	CTT	DL	CPLSD	CPLRT	CStopD	CAS	PLS	CStops	TV	CPUFC	CUFCOE
to Americ	an Metro	Blvd (#3	3)								
Average Before (n=13)	37	1257	18	19	8	26.6	45	0.4	658	12.3	781.6
Std Dev Before (n=13)	13	0	13	o	11	8.3	0	0.5	658	8.8	404.4
Average After (n=14)	24	1257	5	19	0	35.9	45	0	658	5.5	430.3
Std Dev After (n=14)	3	0	3	0	0	3.6	0	0	658	0	23.5
Difference	-13	0	-13	0	-8	9.3	0	-0.4	658	-6.8	-351.3
Std Dev Difference	13	0	13	0	11	9.1	0	0.5	658	8.8	405
% Difference	-35%	0%	-71%	0%	-100%	35.20%	0%	-100.00%	658	-55.40%	-45.00%
to Vetterl	ein Ave (#2)						1			
Average Before (n=13)	68	1507	23	45	10	29.4	40	0.5	675	21	1370.6
Std Dev Before (n=13)	17	0	17	o	13	6.9	0	0.7	675	10.8	509.1
Average After (n=14)	53	1507	8	45	1	35.9	40	0.1	675	13	956.6
Std Dev After (n=14)	7	0	7	0	2	4.4	0	0.3	675	3.9	167.4
Difference	-15	0	-15	0	-9	6.5	0	-0.5	675	-8.1	-414.1
Std Dev Difference	19	0	19	0	13	8.2	0	0.7	675	11.5	535.9
%	-23%	0%	-66%	0%	-94%	22.10%	0%	-86.70%	675	-38.30%	-30.20%
Difference to Whiteh	ead Rd (CR 616) (#1)				1	<u> </u>			<u> </u>
Average Before (n=13)	173	3471	70	104	50	25.7	40	1.5	0	21	1370.6
Std Dev Before (n=13)	29	0	29	0	26	4.4	0	0.7	0	10.8	509.1
Average After (n=14)	117	3471	13	104	3	36.4	40	0.2	0	13	956.6
Std Dev After (n=14)	13	0	13	0	8	3.7	0	0.6	0	3.9	167.4
Difference	-57	0	-57	0	-47	10.7	0	-1.2	0	-8.1	-414.1

Std Dev Difference	32	0	32	0	27	5.8	0	0.9	0	11.5	535.9
% Difference	-33%	0%	-81%	0%	-95%	41.60%	0%	-85.30%	0	-38.30%	-30.20%

Travel Time & Delay Report for Sweet Briar Ave (CR 649) - Weekend MD Peak

Legend:

CTT:

Summarized Cumulative Travel Time since beginning of Run (seconds)

CPI SD:

Summarized Cumulative Posted Speed Limit Delay since beginning of Run (seconds)

CPLRT:

Summarized Cumulative Posted Speed Limit Running Time, or Travel Time since beginning of Run if maintaining Posted Speed Limit (seconds) = accumulation of DL/PLS since beginning of Run

Summarized Cumulative Stopped Delay since beginning of Run (seconds). The *Stopped Delay* is counted from when the speed drops below 5 mph after exceeding 15 mph until it exceeds 15 mph once again

Summarized Cumulative Actual Average Speed since beginning of Run (mph) = CTL/CTT

CStops:

Summarized Cumulative number of Stops in Run. A "Stop" is counted when the speed drops below 5 mph after exceeding 15 mph

Summarized Through Volume (vph)

CPUFC:

Summarized Cumulative Fuel Consumption, from Penic & Upchurch model with TRANSYT7F-10 default coefficients (gal/hr) (= Cumulative (TL/5280*(0.51242*exp(0.024609*DS)/DS) + Delay/3800*(0.0468) + Stops*(3.8424*DS*1.657 + 1.681*DS*1.48922)/1.0E5)*TV) CUFCOE:

Summarized Cumulative Carbon Monoxide Emissions using Synchro 7 formula (from unpublished Oak Ridge National Labs letter to Federal Highway Administration) and University of Florida model for Fuel Consumption (g/hr) (= Cumulative UFFC*69.9)

Cumulative Summary of runs Eastbound from Whitehead Rd (CR 616) (#1)

10 Before-type runs, 10 of unverifiable origin, collected Saturday 10/02/21 to Saturday 10/02/21, over day(s) Sat, with starting times during 1

12 After-type runs, 12 of unverifiable origin, collected Saturday 03/26/22 to Saturday 03/26/22, over day(s) Sat, with starting times during 11:

	CTT	CPLSD	CPLRT	CStopD	CAS	CStops	TV	CPUFC	CUFCOE
to NJ Tra	nsit Haı	milton Rail	Station (#	4)					
Average Before (n=10)	146	40	106	23	29.6	1.3	463	32.6	2091.5
Std Dev Before (n=10)	15	15	0	12	3.4	0.8	463	8.6	342.5
Average After (n=12)	111	5	106	4	38.3	0.3	463	22.4	1528.9
Std Dev After (n=12)	10	10	0	6	3.1	0.5	463	5.1	223.5
Difference	-35	-35	0	-19	8.6	-1	463	-10.2	-562.6
Std Dev Difference	18	18	0	14	4.6	1	463	10	408.9
% Difference	-24%	-88%	0%	-84%	29.20%	-74.40%	463	-31.20%	-26.90%

Cumulative Summary of runs Westbound from NJ Transit Hamilton Rail Station (#4)

10 Before-type runs, 10 of unverifiable origin, collected Saturday 10/02/21 to Saturday 10/02/21, over day(s) Sat, with starting times during 1 11 After-type runs, 11 of unverifiable origin, collected Saturday 03/26/22 to Saturday 03/26/22, over day(s) Sat, with starting times during 11:

	CTT	CPLSD	CPLRT	CStopD	CAS	CStops	TV	CPUFC	CUFCOE
to Whiteh	ead Rd (CR 616) (#	:1)						
Average Before (n=10)	159	55	104	28	27.2	1.1	0	12.5	881.7
Std Dev Before (n=10)	18	18	0	16	3.1	0.3	0	6	296.3
Average After (n=11)	111	8	104	4	37.8	0.5	0	8.7	639.3
Std Dev After (n=11)	7	7	0	5	2.3	0.5	o	0	24.8
Difference	-47	-47	0	-25	10.6	-0.6	0	-3.8	-242.4
Std Dev Difference	20	20	0	17	3.8	0.6	0	6	297.3
% Difference	-30%	-86%	0%	-87%	39.00%	-58.70%	0	-30.30%	-27.50%

Cumulative Summary of all runs, either direction through artery

20 Before-type runs, 20 of unverifiable origin, collected Saturday 10/02/21 to Saturday 10/02/21, over day(s) Sat, with starting times during 1 23 After-type runs, 23 of unverifiable origin, collected Saturday 03/26/22 to Saturday 03/26/22, over day(s) Sat, with starting times during 11:

	CTT	CPLSD	CPLRT	CStopD	CAS	CStops	TV	CPUFC	CUFCOE
to End of	Artery								
Average Before (n=20)	152	47	105	26	28.4	1.2	463	22.6	1486.6
Std Dev Before (n=20)	18	18	1	14	3.4	0.6	463	12.6	694.5
Average After (n=23)	111	6	105	4	38.1	0.4	463	15.9	1103.4
Std Dev After (n=23)	8	8	1	5	2.7	0.5	463	7.9	481.4
Difference	-41	-41	0	-22	9.6	-0.8	463	-6.7	-383.2
Std Dev Difference	19	20	2	15	4.3	0.8	463	14.8	845
% Difference	-27%	-87%	0%	-85%	33.90%	-67.40%	463	-29.60%	-25.80%

Summary of runs Eastbound from Whitehead Rd (CR 616) (#1)

10 Before-type runs, 10 of unverifiable origin, collected Saturday 10/02/21 to Saturday 10/02/21, over day(s) Sat, with starting times during 11:26:48 AM to 1:53:37 PM 12 After-type runs, 12 of unverifiable origin, collected Saturday 03/26/22 to Saturday 03/26/22, over day(s) Sat, with starting times during 11:05:54 AM to 1:52:44 PM

				turday 03/26/							
Node	CTT	DL	CPLSD	CPLRT	CStopD	CAS	PLS	<u>CStops</u>	TV	<u>CPUFC</u>	CUFCOE
	ein Ave (#	2)									
Average Before (n=10)	70	3471	11	59	4	34.5	40	0.3	473	13.9	953.1
Std Dev Before (n=10)	7	0	7	0	6	3.2	0	0.5	473	5	212
Average After (n=12)	58	3471	-1	59	0	41	40	0	473	10.7	769.1
Std Dev After (n=12)	3	0	3	0	0	1.8	0	0	473	0	18.3
Difference	-12	0	-12	0	-4	6.5	0	-0.3	473	-3.2	-184
Std Dev Difference	8	0	8	0	6	3.7	0	0.5	473	5	212.8
% Difference	-17%	0%	-113%	0%	-100%	18.80%	0%	-100.00%	473	-23.10%	-19.30%
	an Metro	Blvd (#3)									
Average Before (n=10)	102	1507	17	85	7	33.7	40	0.7	478	22.7	1473.4
Std Dev Before (n=10)	11	0	11	0	8	3.3	0	0.8	478	8.7	350.4
Average After (n=12)	90	1507	5	85	4	38	40	0.3	478	18.7	1252.1
Std Dev After (n=12)	9	0	9	0	6	3.8	0	0.5	478	5.1	218.5
Difference	-13	0	-13	0	-3	4.3	0	-0.4	478	-4	-221.3
Std Dev Difference	14	0	14	0	10	5	0	1	478	10.1	413
% Difference	-12%	0%	-73%	0%	-46%	12.70%	0%	-52.40%	478	-17.70%	-15.00%
to NJ Tra	nsit Hamil	ton Rail S	tation (#4)								
Average Before (n=10)	146	1257	40	106	23	29.6	40	1.3	463	32.6	2091.5
Std Dev Before (n=10)	15	0	15	0	12	3.4	0	0.8	463	8.6	342.5
Average After (n=12)	111	1257	5	106	4	38.3	40	0.3	463	22.4	1528.9
Std Dev After (n=12)	10	0	10	0	6	3.1	0	0.5	463	5.1	223.5
Difference	-35	0	-35	0	-19	8.6	0	-1	463	-10.2	-562.6
Std Dev Difference	18	0	18	0	14	4.6	0	1	463	10	408.9
% Difference	-24%	0%	-88%	0%	-84%	29.20%	0%	-74.40%	463	-31.20%	-26.90%

Summary of runs Westbound from NJ Transit Hamilton Rail Station (#4)

10 Before-type runs, 10 of unverifiable origin, collected Saturday 10/02/21 to Saturday 10/02/21, over day(s) Sat, with starting times during 11:01:29 AM to 1:46-58 PM

11 After-type runs, 11 of unverifiable origin, collected Saturday 03/26/22 to Saturday 03/26/22, over day(s) Sat, with starting times during 11:02:19 AM to 1:47-56 PM

Node	CTT	DL	CPLSD	CPLRT	CStopD	CAS	PLS	CStops	TV	CPUFC	CUFCOE
to Americ	an Metro	Blvd (#3)									
Average Before (n=10)	30	1257	11	19	3	30.4	45	0.2	501	6.9	460.3
Std Dev Before (n=10)	8	o	8	o	6	6.1	o	0.4	501	5.5	240.6
Average After (n=11)	22	1257	3	19	0	39.1	45	0	501	4.2	315
Std Dev After (n=11)	2	0	2	0	0	3.2	0	0	501	0	13.7
Difference	-8	0	-8	0	-3	8.8	0	-0.2	501	-2.7	-145.4
Std Dev Difference	8	0	8	0	6	6.9	o	0.4	501	5.5	241
% Difference	-26%	0%	-70%	0%	-100%	28.90%	0%	-100.00%	501	-38.90%	-31.60%
	ein Ave (#	2)									
Average Before (n=10)	64	1507	19	45	5	30.5	40	0.3	479	12.5	881.7
Std Dev Before (n=10)	15	0	15	0	9	6.3	0	0.5	479	6	296.3
Average After (n=11)	47	1507	2	45	0	39.8	40	0	479	8.7	639.3
Std Dev After (n=11)	4	0	4	0	0	2.9	o	o	479	0	24.8
Difference	-17	0	-17	0	-5	9.2	0	-0.3	479	-3.8	-242.4
Std Dev Difference	15	0	15	0	9	7	0	0.5	479	6	297.3
% Difference	-27%	0%	-88%	0%	-100%	30.20%	0%	-100.00%	479	-30.30%	-27.50%
	ead Rd (C	R 616) (#1)								
Average Before (n=10)	159	3471	55	104	28	27.2	40	1.1	0	12.5	881.7
Std Dev Before (n=10)	18	0	18	0	16	3.1	o	0.3	0	6	296.3
Average After (n=11)	111	3471	8	104	4	37.8	40	0.5	0	8.7	639.3

Std Dev After (n=11)	7	0	7	0	5	2.3	o	0.5	o	o	24.8
Difference	-47	0	-47	0	-25	10.6	0	-0.6	0	-3.8	-242.4
Std Dev Difference	20	0	20	0	17	3.8	0	0.6	o	6	297.3
% Difference	-30%	0%	-86%	0%	-87%	39.00%	0%	-58.70%	0	-30.30%	-27.50%

Appendix B

Sloan Avenue (C.R.649) and Klockner Road

Hamilton Township, Mercer County, New Jersey Equipment ID SG01350



CONTROLLER TIMING

PHASE	Ø 1	Ø2	Øз	Ø 4	Ø 5	Ø 6	Ø7	Ø 8
MINIMUM		30		10		30		10
EXTENSION		2.0		2.0		2.0		2.0
MAX I		40		24		40		36
MAX II								
PED WALK		7				7		7
PED CLEAR		22				22		17
YELLOW		5.0		4.0		5.0		4.0
RED		2.0		2.0		2.0		2.0
MIN RECALL		ON		OFF		ON		OFF
PED RECAL		OFF		OFF		OFF		OFF
MAX RECALL		OFF		OFF		OFF		OFF
MEMORY		OFF		OFF		OFF		OFF
FLASH		Υ		R		Υ		R

Ø 2 Sloan Avenue EB

Ø 4 Klockner Road

Ø 6 Sloan Avenue WB

Ø 8 NJ Transit Complex Exit

CONTROLLER NOTES:

- 1) The manual control shall be disconnected.
- 2) Signal shall rest in phases 2 and 6 green.
- 3) Phase 4 and phase 8 are timed seperately and may be skipped in the absence of vehicular or pedestrian demand.

Sloan Avenue (C.R.649) and American Metro Boulevard

Hamilton Township, Mercer County, New Jersey Equipment ID SG01340



CONTROLLER TIMING

PHASE	Ø1	Ø 2	Ø 3	Ø 4	Ø 5	Ø 6	Ø 7	Ø 8	OVLP A	OVLP B	OVLP C
MINIMUM	7	21		7	7	21					
EXTENSION	2.0			2.0	2.0						
MAX I	10	21		20	10	21					
MAX II											
PED WALK		35		7		35					
PED CLEAR		19		13		8					
YELLOW	4.0	4.0		3.0	4.0	4.0					
RED		3.0		3.0		3.0					
MIN RECALL	OFF	OFF		OFF	OFF	OFF					
PED RECAL	OFF	OFF		OFF	OFF	OFF					
MAX RECALL	OFF	OFF		OFF	OFF	OFF					
MEMORY	OFF	OFF		OFF	OFF	OFF					
C.N.A.	OFF	ON		OFF	OFF	ON					
FLASH		Υ		R					Υ		

Ø 1	Sloan Avenue EB Lead Left
d 2	Sloan Avenue WR R O W

Ø 4 American Metro Boulevard

Ø 5 Dummy Phase (Times with phase 1 to hold phase 6 pedestrian timer)

Ø 6 Dummy Phase (Start of pedestrian clearance activates Red Signal Ahead sign)

OVLP A Sloan Avenue EB R.O.W. (Parent Phases 1+2)

OVLP B American Metro Boulevard Right Turn (Parent Phases 1+4)

OVLP C Sloan Avenue WB Right Turn (Parent Phase 4)

CONTROLLER NOTES:

- 1) The signal shall rest in the Sloan Avenue R.O.W. walk.
- 2) Phase 1 shall only follow phase 4.
- 3) Sloan Avenue R.O.W. must follow phase 1.

Sweetbriar Road (C.R.649) and Vetterlein Avenue

Hamilton Township, Mercer County, New Jersey Equipment ID SG01330



CONTROLLER TIMING

PHASE	Ø1	Ø2	ØЗ	Ø 4	Ø 5	Ø 6	Ø7	Ø 8
MINIMUM	6	60		6		60		
EXTENSION				2.0				
MAX I	6	60		20		60		
MAX II								
PED WALK								
PED CLEAR								
YELLOW	3.0	4.0		3.0		4.0		
RED		2.0		2.0		2.0		
MIN RECALL	ON	OFF		OFF		OFF		
PED RECAL	OFF	OFF		OFF		OFF		
MAX RECALL	OFF	ON		OFF		ON		
MEMORY	OFF	OFF		OFF		OFF		
FLASH		Υ		R		Υ		

Ø 1 Sweetbriar Road EB Lead LeftØ 2 Sweetbriar Road WB R.O.W.

Ø 4 Vetterlein Avenue

Ø 6 Sweetbriar Road EB R.O.W.

CONTROOLER NOTES:

- 1) The manual control shall be disconnected.
- 2) Signal shall rest in phase 2 and 6 green.
- 3) Lead left phase 1 shall only follow phase 4.
- 4) Sweetbriar Road R.O.W. (2 and 6) must follow phase 1.

Whitehead Road (C.R.616) and Sweetbriar Avenue (C.R.649)

Hamilton Township, Mercer County, New Jersey Equipment ID SG00950



CONTROLLER TIMING

PHASE	Ø 1	Ø2	ØЗ	Ø 4	Ø 5	Ø6	Ø7	Ø 8
MINIMUM		15		6				6
EXTENSION		2.0		2.0				2.0
MAX I		31		20				20
MAX II								
PED WALK				5				7
PED CLEAR				18				13
YELLOW		5.0		4.0				4.0
RED		2.0		2.0				2.0
MIN RECALL		ON		OFF				OFF
PED RECAL		OFF		OFF				OFF
MAX RECALL		OFF		OFF				OFF
MEMORY		OFF		OFF				OFF
FLASH		Υ		R				R

Ø 2 Whitehead Road SB

Ø 4 Whitehead Road NB

Ø 8 Sweetbriar Avenue

CONTROLLER NOTES:

- 1) The memory circuits shall be off.
- 2) Signal shall rest in phase 2 green.

Appendix C

Implemented Timings

New Jersey Traffic Signal Retiming Initiative

Sloan Ave & Sweet Briar Ave (CR 649) Mercer County, New Jersey

Prepared for:
Delaware Valley Regional Planning Commission (DVRPC)



and

Mercer County, NJ




Prepared by:



Subcontracted with:





Hourly Volumes - Average for Three Count Locations on Sloan Ave/Sweet Briar Ave (CR 649)



Flow Rate (veh/hr)

Flow Rate (veh/hr)



Hourly Volumes - Sweet Briar Ave (CR 649) West of Rutgers Ave



Flow Rate (veh/hr)

Flow Rate (veh/hr)





Hourly Volumes - Sweet Briar Ave (CR 649) West of Sandalwood Ave



Flow Rate (veh/hr)

Flow Rate (veh/hr)





Hourly Volumes - Sloan Ave (CR 649) West of Klockner Ave



Flow Rate (veh/hr)

Flow Rate (veh/hr)





EXISTING SCHEDULES

Sloan Ave & Sweet Briar Ave (CR 649) Weekday

1	Whitehead Rd	(CR 616)
---	--------------	----------

- 2 Vetterlein Ave
- 3 American Metro Blvd
- 4 Klockner Ave/NJ Transit H.R.S

)		12 aı
	0 [Free]	

IMPLEMENTED SCHEDULES

Sloan Ave & Sweet Briar Ave (CR 649) Weekday

- 1 Whitehead Rd (CR 616)
- 2 Vetterlein Ave
- 3 American Metro Blvd
- 4 Klockner Ave/NJ Transit H.R.S

12 an 1 an	7 am 8 am	9 all 10 al 11 al	12 p 1 pm 2 pm	3 pm 4 pm 5 pm	7 pm	8 pm 9 pm 10 p 11 p
254 [Free]	1 [90]	254 [FREE]	2 [80]	3 [90]	4 [80]	254 [FREE]
254 [Free]	1 [90]	254 [FREE]	2 [80]	3 [90]	4 [80]	254 [FREE]
254 [Free]	1 [90]	2	2 [80]	3 [90]	4 [80]	254 [FREE]
254 [Free]	1 [90]	2	2 [80]	3 [90]	4 [80]	254 [FREE]

EXISTING SCHEDULES

Sloan Ave & Sweet Briar Ave (CR 649) Saturday

- 1 Whitehead Rd (CR 616)
- 2 Vetterlein Ave
- 3 American Metro Blvd
- 4 Klockner Ave/NJ Transit H.R.S

)	112 am 1 a	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
	0 [Free]	

- 1 Whitehead Rd (CR 616)
- 2 Vetterlein Ave
- 3 American Metro Blvd
- 4 Klockner Ave/NJ Transit H.R.S

IMPLEMENTED SCHEDULES Sloan Ave & Sweet Briar Ave (CR 649) Saturday	12 am 	12 am 1 am 2 am 3 am 4 am 5 am 6 am 7 am 8 am 11 am										11 am	12 pm 12 pm 1 pm 2 pm 3 pm			4 pm	- 4 pm 5 pm 6 pm 7 pm 8 pm 9 pm 10 pm 11 pm 12 am					12 am		
1 Whitehead Rd (CR 616)		254 [Free]										6 [80]				254 [FREE]								
2 Vetterlein Ave		254 [Free]										6 [80]					254 [FREE]							
3 American Metro Blvd		254 [Free]								5	[70]		6 [80]				5 [70]				254 [FREE]			
4 Klockner Ave/NJ Transit H.R.S		254 [Free]								5	[70]		6 [80]					5 [70]		254 [FREE]			1

EXISTING SCHEDULES

Sloan Ave & Sweet Briar Ave (CR 649) Sunday

- 1 Whitehead Rd (CR 616)
- 2 Vetterlein Ave
- 3 American Metro Blvd
- 4 Klockner Ave/NJ Transit H.R.S

7	11 am 12 am 13 am 14 am 6 am 10 am 11 am 12 pm 1 pm 1 pm 1 pm 1 pm 1 pm 1 pm 1 pm													
0 [Free]														
	0 [Free]													
0 [Free]														
	0 [Free]													

IMPLEMENTED SCHEDULES

Sloan Ave & Sweet Briar Ave (CR 649) Sunday

- 1 Whitehead Rd (CR 616)
- 2 Vetterlein Ave
- 3 American Metro Blvd
- 4 Klockner Ave/NJ Transit H.R.S

12 a	ס ס	3 an	4 an	5 an	6 an	7 an	8 an	9 an	10 a	11 a	12 p	1 pn	2 pn	3 pn	4 pn	5 pn	e pn	7 pn	8 pn	9 pn	10 p	11 p	12 a
	254 [Free]											6 [80]			254 [FREE]							
	254 [Free]											6 [80]			254 [FREE]							
	254 [Free] 5 [70]											6 [80]				5 [70]		254 [FREE]			

6 [80]

5 [70]

254 [FREE]


5 [70]

254 [Free]
















Phase Diagrams


Permissive Movement


Protected + Permissive Movement


↑ Protected-Only Movement











AM Peak	Existing	Implemented	Difference
Total Delay (hr)	35	32	-8.6%
Total Stops	3,982	3,627	-8.9%
Total Travel Time (hr)	96	94	-2.1%
Fuel Consumed (gal)	152	146	-3.9%
MD Peak	Existing	Implemented	Difference
Total Delay (hr)	30	22	-26.7%
Total Stops	2,404	2,069	-13.9%
Total Travel Time (hr)	73	65	-11.0%
Fuel Consumed (gal)	106	97	-8.5%
PM Peak	Existing	Implemented	Difference
Total Delay (hr)	50	44	-12.0%
Total Stops	4,475	4,134	-7.6%
Total Travel Time (hr)	117	110	-6.0%
Fuel Consumed (gal)	173	165	-4.6%
PM Off-peak	Existing	Implemented	Difference
PM Off-peak Total Delay (hr)	Existing 21	Implemented 19	Difference -9.5%
·		-	
Total Delay (hr)	21	19	-9.5%
Total Delay (hr) Total Stops	21 2,565	19 2,278	-9.5% -11.2%
Total Delay (hr) Total Stops Total Travel Time (hr)	21 2,565 63	19 2,278 61	-9.5% -11.2% -3.2%
Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal)	21 2,565 63 98	19 2,278 61 94	-9.5% -11.2% -3.2% -4.1%
Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak	21 2,565 63 98 Existing	19 2,278 61 94 Implemented	-9.5% -11.2% -3.2% -4.1% Difference
Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak Total Delay (hr)	21 2,565 63 98 Existing	19 2,278 61 94 Implemented 13	-9.5% -11.2% -3.2% -4.1% Difference -7.1%
Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak Total Delay (hr) Total Stops	21 2,565 63 98 Existing 14 1,974	19 2,278 61 94 Implemented 13 1,691	-9.5% -11.2% -3.2% -4.1% Difference -7.1% -14.3%
Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak Total Delay (hr) Total Stops Total Travel Time (hr)	21 2,565 63 98 Existing 14 1,974 51	19 2,278 61 94 Implemented 13 1,691 49	-9.5% -11.2% -3.2% -4.1% Difference -7.1% -14.3% -3.9%
Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal)	21 2,565 63 98 Existing 14 1,974 51	19 2,278 61 94 Implemented 13 1,691 49 77	-9.5% -11.2% -3.2% -4.1% Difference -7.1% -14.3% -3.9% -4.9%
Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend MD Peak	21 2,565 63 98 Existing 14 1,974 51 81 Existing	19 2,278 61 94 Implemented 13 1,691 49 77 Implemented	-9.5% -11.2% -3.2% -4.1% Difference -7.1% -14.3% -3.9% -4.9% Difference
Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend MD Peak Total Delay (hr)	21 2,565 63 98 Existing 14 1,974 51 81 Existing 18	19 2,278 61 94 Implemented 13 1,691 49 77 Implemented 16	-9.5% -11.2% -3.2% -4.1% Difference -7.1% -14.3% -3.9% -4.9% Difference -11.1%







Synchro Intersection Delay Summary:

Number of intersections where:	AM	MD	PM	РО	WA	WM
delay decreased	3	3	4	3	3	3
delay increased ≤ 5 sec/veh	1	1	0	1	1	1
delay increased > 5 sec/veh	0	0	0	0	0	0

	Intersection Delay and LOS Summary																									
			АМ			MD		PM			РО			WA			WM		М							
ľ	nt. ID	Side Street	Dela	y (hr)	Int.	LOS	Dela	y (hr)	Int.	LOS	Dela	y (hr)	Int.	LOS	Dela	y (hr)	Int.	LOS	Dela	y (hr)	Int.	LOS	Dela	y (hr)	Int.	LOS
			Ex	Imp	Ex	lmp	Ex	Imp	Ex	Imp																
	1	Whitehead Rd (CR 616)	25	26	С	С	52	34	D	С	40	35	D	С	16	17	В	В	17	19	В	В	16	17	В	В
	2	Vetterlein Ave	9	8	Α	Α	3	3	Α	Α	7	7	Α	Α	6	4	Α	Α	6	3	Α	Α	6	4	Α	Α
	3	American Metro Blvd	14	11	В	В	9	6	Α	Α	16	13	В	В	7	6	Α	Α	8	6	Α	Α	9	7	Α	Α
ΙĹ	4	Klockner Ave/NJ Transit Hamilton Rail Station	20	18	С	В	16	15	В	В	22	22	C	С	22	20	C	В	16	13	В	В	17	15	В	В









AM Peak	Existing	Implemented	Difference			
Total Delay (hr)	36	35	-1.7%			
Total Stops	3,033	2,674	-11.8%			
Total Travel Time (hr)	121	121	-0.2%			
Fuel Consumed (gal)	112	112	0.0%			
MD Peak	Existing	Implemented	Difference			
Total Delay (hr)	24	23	-4.2%			
Total Stops	2,002	1,893	-5.4%			
Total Travel Time (hr)	84	83	-0.6%			
Fuel Consumed (gal)	78	77	-0.6%			
PM Peak	Existing	Implemented	Difference			
Total Delay (hr)	50	47	-5.6%			
Total Stops	3,831	3,627	-5.3%			
Total Travel Time (hr)	143	141	-1.3%			
Fuel Consumed (gal)	126	124	-1.3%			
1 10-7						
PM Off-peak	Existing	Implemented	Difference			
ισ ,	Existing 21	Implemented 20	Difference -4.8%			
PM Off-peak		-				
PM Off-peak Total Delay (hr)	21	20	-4.8%			
PM Off-peak Total Delay (hr) Total Stops	21 2,032	20 1,888	-4.8% -7.1%			
PM Off-peak Total Delay (hr) Total Stops Total Travel Time (hr)	21 2,032 83	20 1,888 82	-4.8% -7.1% -0.8%			
PM Off-peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal)	21 2,032 83 79	20 1,888 82 78	-4.8% -7.1% -0.8% -1.8%			
PM Off-peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak	21 2,032 83 79 Existing	20 1,888 82 78 Implemented	-4.8% -7.1% -0.8% -1.8% Difference			
PM Off-peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak Total Delay (hr)	21 2,032 83 79 Existing	20 1,888 82 78 Implemented 13	-4.8% -7.1% -0.8% -1.8% Difference -7.8%			
PM Off-peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak Total Delay (hr) Total Stops	21 2,032 83 79 Existing 14 1,490	20 1,888 82 78 Implemented 13 1,420	-4.8% -7.1% -0.8% -1.8% Difference -7.8% -4.7%			
PM Off-peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak Total Delay (hr) Total Stops Total Travel Time (hr)	21 2,032 83 79 Existing 14 1,490 65	20 1,888 82 78 Implemented 13 1,420 65	-4.8% -7.1% -0.8% -1.8% Difference -7.8% -4.7% -0.5%			
PM Off-peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal)	21 2,032 83 79 Existing 14 1,490 65	20 1,888 82 78 Implemented 13 1,420 65 63	-4.8% -7.1% -0.8% -1.8% Difference -7.8% -4.7% -0.5%			
PM Off-peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend MD Peak	21 2,032 83 79 Existing 14 1,490 65 64 Existing	20 1,888 82 78 Implemented 13 1,420 65 63 Implemented	-4.8% -7.1% -0.8% -1.8% Difference -7.8% -4.7% -0.5% Difference			
PM Off-peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend AM Peak Total Delay (hr) Total Stops Total Travel Time (hr) Fuel Consumed (gal) Weekend MD Peak Total Delay (hr)	21 2,032 83 79 Existing 14 1,490 65 64 Existing 19	20 1,888 82 78 Implemented 13 1,420 65 63 Implemented 19	-4.8% -7.1% -0.8% -1.8% Difference -7.8% -4.7% -0.5% -0.5% Difference -1.6%			























Eastbound : Whitehead Rd (CR 616) to NJ Transit Hamilton Rail Station Westbound : NJ Transit Hamilton Rail Station to Whitehead Rd (CR 616)










Figure 21
Average Travel Time & Delay
Sloan Ave & Sweet Briar Ave (CR 649)

Mercer County, NJ - Sloan Ave & Sweet Briar Ave (CR 649) Detection/Observation Summary

	_		_	
ID	Intersection	Controller Type	Communication Type & Controller Date/Time Status During Field Notes (Nov '21)	Notes/Issue Summary from Initial Field Notes (Observed 11/23/2021)
1	Sweet Briar Ave (CR 649) & Whitehead Rd (CR 616)	Econolite ASC/3	No GPS or comm. Date OK. Time 3 seconds fast.	Pedestrian pushbutton on southeast corner for pedestrian Ø4 (northbound) does not place call in controller. Pedestrian display on northeast corner for pedestrian Ø8 (westbound) not displaying countdown.
2	Sweet Briar Ave (CR 649) & Vetterlein Ave	Econolite ASC/3	No GPS or comm. Date OK.	Cabinet had snake and spider infestation during field notes in November but was cleared out mostly by implementation in March. A couple snakes were in cabinet along with many large spiders. May be worth clearing out and stuffing the conduit with copper or other sealant. Ø4 (southbound) was showing intermittent false calls during our observations. Could be due to either shadows or picking up calls from the adjacent lanes. Either way, there were several cycles where the side street serviced with no demand, so worth reviewing detector zone. Ø1 (eastbound left-turn), Ø2 (westbound) and Ø6 (eastbound) have no detection and showing no calls in controller (not an issue, just observation for free operation behavior).
3	Sweet Briar Ave-Sloan Ave (CR 649) & American Metro Blvd	Econolite ASC/3	No GPS or comm.	Ø1 (eastbound left-turn) has a constant call on video detection, so will service each cycle regardless of demand and utilize all allotted time to that phase. Ø2 (westbound) and Ø6 (eastbound) have no detection and showing no calls in controller (not an issue, just observation for free operation behavior). Wiring and programming of the cabinet is unique as there are several enabled dummy phases that run with overlaps (Ø5 and Ø6). Pedestrian button on the northwest corner for pedestrian Ø4 (southbound) does not place call in controller. UPS in cabinet not functioning as it is clearly turned off. Rodents were in cabinet during implementation, clear nest in back of cabinet.
4	Sloan Ave (CR 649) & NJ Transit Hamilton Rail Station-Klockner Ave	Econolite ASC/3	No GPS or comm. Date OK. Time 3 seconds fast.	Pedestrian pushbutton missing on southwest corner for pedestrian Ø8 (southbound). Looks to have been hit by a turning truck and knocked off pole. Rodents were in cabinet during implementation, clear nest in back of cabinet.